

GIGABYTE G481-HAO 4U SERVER



EIGENSCHAPPEN

- Supports 5G network infrastructure
- Up to 10 x NVIDIA Tesla® V100 PCIe GPGPU cards
- 2nd Gen. Intel® Xeon® Scalable and Intel® Xeon® Scalable Processors
- Intel® Omni-Path architecture technology support as an option
- 6-Channel RDIMM/LRDIMM DDR4, 24 x DIMMs
- Supports Intel® Optane™ DC Persistent Memory
- 2 x 10Gb/s BASE-T LAN ports (Intel® X550-AT2)
- 2 x GbE LAN ports (Intel® I350-AM2)
- 8 x NVMe, 2 x SATA/SAS 2.5" hot-swappable HDD/SSD bays
- 12 x 3.5" SATA/SAS hot-swappable HDD/SSD bays
- 2 x low profile PCIe Gen3 expansion slots
- Aspeed® AST2500 remote management controller
- 3 x 80 PLUS Platinum 2200W redundant PSU
- Optimized performance with Mellanox Infiniband EDR and Ethernet 100G products
- Aspeed® AST2500 remote management controller
- 4 x 80 PLUS Platinum 2200W 2+2 redundant PSU
- Optimized performance with Mellanox Infiniband EDR and Ethernet 100G products



SPECIFICATIES

Dimensions (WxHxD, mm)	4U 448 x 176 x 880
Motherboard	MG61-G40
CPU	2nd Generation Intel® Xeon® Scalable and Intel® Xeon® Scalable Processors Intel® Xeon® Platinum Processor, Intel® Xeon® Gold Processor, Intel® Xeon® Silver Processor and Intel® Xeon® Bronze Processor NOTE: If only 1 CPU is installed, some PCIe or memory functions might be unavailable
Socket	2 x LGA 3647 Socket P TDP up to 205W
Chipset	Intel® C621 Express Chipset
Memory	24 x DIMM slots DDR4 memory supported only 6-channel memory architecture RDIMM modules up to 64GB supported LRDIMM modules up to 128GB supported Supports Intel® Optane™ DC Persistent Memory (DCPMM) 1.2V modules: 2933/2666/2400/2133 MHz Maximum verified DCPMM configuration: * Ambient temperature 35°C * 2nd Generation Intel® Xeon® Scalable processor 205W (Max.) * DCPMM 256GB x12 pcs DCPMM installation locations: DIMM_P0_(A1, B1, C1) DIMM_P0_(D1, E1, F1) DIMM_P1_(G1, H1, I1) DIMM_P1_(J1, K1, L1) NOTE: 1. 2933MHz for 2nd Generation Intel® Xeon® Scalable Processors only 2. Intel® Optane™ DC Persistent Memory for 2nd Generation Intel® Xeon® Scalable Processors only 3. The maximum number of DCPMM that can be installed is based on a maximum operating (ambient) temperature of 35°C 4. To enquire about installing a greater number of DCPMM, please consult with your GIGABYTE technical or sales representative



LAN	<p>Rear Side: 2 x 10Gb/s BASE-T LAN ports (Intel® X550-AT2) 1 x 10/100/1000 management LAN</p> <p>Front Side: 2 x 1Gb/s BASE-T LAN ports (Intel® I350-AM2) * 4 x QSFP28 LAN ports with Intel® Omni-Path Host Fabric Interface (as an option) - Provides 25Gb/s bandwidth per port, total 100Gb/s bandwidth with 4 QSFP28 LAN ports * NOTE: Please select Intel® Xeon processors with Omni-Path Architecture to enable Intel® Omni-Path Host Fabric Interface</p>
Video	<p>Integrated in Aspeed® AST2500 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM</p>
Storage	<p>12 x 3.5" hot-swappable HDD/SSD bays - Compatible with SATA/SAS devices only 10 x 2.5" hot-swappable HDD/SSD bays - 8 x amber HDD trays compatible with NVMe or SATA/SAS devices - 2 x blue HDD trays compatible with SATA/SAS devices only Pre-install with Broadcom SAS3008 storage adapter with IR mode and expander board Bandwidth: SATAIII 6Gb/s or SAS 12Gb/s per port</p>
SATA	Supported
SAS	Supported
RAID	<p>For SATA/SAS drives: Pre installed Broadcom SAS3008 SAS Card Software RAID, IR mode For NVMe drives: Intel® Virtual RAID On CPU (VROC) RAID 0, 1, 10, 5 Note: VROC module is compatible for Intel®SSD only</p>
Peripheral Drives	-
Expansion Slots	<p>10 x PCIe x16 slots (Gen3 x16 bus) for GPUs 1 x PCIe x16 (Gen3 x8 bus) Half-length low-profile slot in front, occupied by CRA3338 HBA 1 x PCIe x16 (Gen3 x16 bus) Half-length low-profile slot at rear - System is validated for population with a uniform GPU model - Support is not provided for mixed GPU populations</p>
Internal I/O	<p>1 x TPM header 1 x VROC connector 1 x Front VGA header 1 x Serial header</p>



Front I/O	<ul style="list-style-type: none"> 2 x USB 3.0 1 x VGA 2 x RJ45 1 x MLAN (Reserved, enabled by cable switch) 4 x Omni-Path QSFP28 LAN ports (Reserved) 1 x Power button with LED 1 x ID button with LED 1 x Reset button 1 x NMI button 1 x System status LED 1 x HDD access LED 1 x Omni-Path activity LED
Rear I/O	<ul style="list-style-type: none"> 2 x RJ45 1 x MLAN (Primary port)
Backplane I/O	12 x 3.5" ports and 10 x 2.5" ports
TPM	<ul style="list-style-type: none"> 1 x TPM header with SPI interface
	Optional TPM2.0 kit: CTM010
Power Supply	<ul style="list-style-type: none"> 3 x 2200W redundant PSUs 80 PLUS Platinum AC Input: <ul style="list-style-type: none"> - 100-127V~/ 14A, 47-63Hz - 200-240V~/ 12.6A, 47-63Hz DC Output: <ul style="list-style-type: none"> - Max 1200W/ 100-127V~ +12.12V/ 95.6A +12Vsb/ 3.5A - Max 2200W/ 200-240V +12.12V/ 178.1A +12Vsb/ 3.5A NOTE: The system power supply requires C19 type power cord
System Management	<ul style="list-style-type: none"> Aspeed® AST2500 management controller Avocent® MergePoint IPMI 2.0 web interface: <ul style="list-style-type: none"> Network settings Network security settings Hardware information Users control Services settings IPMI settings Sessions control LDAP settings Power control Fan profiles Voltages, fans and temperatures monitoring System event log Events management (platform events, trap settings, email settings) Serial Over LAN vKVM & vMedia (HTML5)



OS Supported	<p>For Skylake processors: Windows Server 2012 R2 with Update Windows Server 2016 Windows Server 2019 Red Hat Enterprise Linux 6.9 (x64) or later Red Hat Enterprise Linux 7.3 (x64) or later Red Hat Enterprise Linux 8.0 (x64) or later SUSE Linux Enterprise Server 11.4 (x64) or later SUSE Linux Enterprise Server 12.2 (x64) or later SUSE Linux Enterprise Server 15 (x64) or later Ubuntu 16.04.1 LTS (x64) or later Ubuntu 18.04 LTS (x64) or later VMware ESXi 6.0 Update3 or later VMware ESXi 6.5 or later VMware ESXi 6.7 or later VMware ESXi 7.0 or later Citrix Xenserver 7.1.0 CU2 or later Citrix Xenserver 7.4.0 or later Citrix Hypervisor 8.0.0 or later</p> <p>For Cascade Lake processors: Windows Server 2012 R2 with Update Windows Server 2016 Windows Server 2019 Red Hat Enterprise Linux 7.6 (x64) or later Red Hat Enterprise Linux 8.0 (x64) or later SUSE Linux Enterprise Server 12.3 (x64) or later SUSE Linux Enterprise Server 15 (x64) or later Ubuntu 18.04 LTS (x64) or later VMware ESXi 6.0 Update3 or later VMware ESXi 6.5 Update2 or later VMware ESXi 6.7 Update1 or later VMware ESXi 7.0 or later Citrix Xenserver 7.1.0 CU2 or later Citrix Xenserver 7.5.0 or later Citrix Hypervisor 8.0.0 or later</p>
Weight	Net Weight: 39 kg Gross Weight: 58.1 kg
System Fans	4 x 40x40x28mm (25,000rpm) 6 x 60x60x76mm (21,700rpm)
Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8%-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing) NOTE: Please contact Technical Support for more information about optimized GPU system operating temperature
Packaging Content	1 x G481-HA0 2 x CPU heatsinks 1 x Rail kit 1 x VROC module 2 x Non-Fabric CPU carrier



Part Numbers

Barebone with rail kit: 6NG481HA0MR-00

- Motherboard: 9MG61G40NR-00
- VROC module: 25FD0-R181N0-10R
- Rail kit: 25HB2-420100-CGR
- CPU heatsink: 25ST1-323206-A0R
- Fan module kit: 6NG481HAASR-00-100
- Storage adapter: 9CRA3338NR-00
- Power supply: 25EP0-222001-D0S
- C19 type power cord 125V/15A (US): 25CP1-018000-Q0R (optional)
- C19 type power cord 250V/16A (EU): 25CP3-01830H-Q0R (optional)
- C19 type power cord 250V/15A (US): 25CP1-018300-Q0R (optional)